

2305/A Pro Enforcer Low Shoe

POLICE & MILITARY



- Operational uniform shoe suitable for law enforcement units and for civil protection operators
- Extremely lightweight and comfortable for long-day usage
- Good stability and excellent grip for running and walking on uneven grounds
- Upper fabric 100% warp-knitted PA coupled with perforated microfiber to ensure a good resistance and a good overall breathability
- Three-dimensional 100% PES inner lining: high abrasion and tear resistance values
- High breathability upper and lining (800% higher than the European Standard EN ISO 20347 5.4.6)
- Speed-lacing system using textured PES webbing with added nylon
- High performance outsole made of special nitrile rubber, resistant to heat and fuel oil, antistatic, SRC slip resistance with high abrasion resistance
- Soft PU midsole that provides a shock absorbing effect
- Textile anti-perforation insole: it offers high resistance to penetration and also provides flexibility to the footwear, heat insulation, moisture absorption
- Anatomically shaped footbed designed to increase the comfort of the foot morphology
- Heat insulation is 40% higher than the European Standard EN ISO 20347 6.2.3.1
- The energy absorption in the heel area is 50% higher than the European Standard EN ISO 20347 6.2.4



Product name: Pro Enforcer Low Shoe

Article number: 2305/A

Upper leather

Cordura® PA fabric, water repellent, black, lined with perforated microfiber to ensure stability and breathability. The upper is completed by two lateral abrasion resistant light microfiber overlays and a weave of polyurethane material bands

Tongue and bellow

Cordura® PA fabric, lined with a lightweight water-repellent black felt. The tongue is padded with a high-density cross-linked polyurethane foam that provides both comfort and high breathability.

Lining

Three-dimensional 100% PES fabric, black colour, with high abrasion and tear resistance.

Toe Cap

Extruded polyurethane and synthetic fibres impregnated with thermo-adhesive resins with a thickness of 1.35 mm.

Heel Cap

1,50mm resin bonded synthetic fabric, thermally mouldable, glued to upper material.

Heel

Suede microfiber black colour, thickness mm 1,0.

Lacing system

Fast Lacing system: 3 pairs of tape eyelets and 1 pair of eyelets at the top of the upper, for optimal lacing without friction.

The tape eyelets are made of textured PES added with nylon so that the material is elastic and resistant. The eyelets are made of brass material to avoid oxidation problems.

Sewing thread

Water-repellent treated polyester 30/3 yarn, black.

Lacets

Round, 100%, recycled polyester, water repellent treated, black.

Footbed

Pre-shaped footbed, designed to give a shock-absorber effect in the central area of the sole, inner side and heel.

The footbed is lined with abrasion resistant fabric and made of highly breathable, open-cell polyurethane foam that does not lose its shape, its lightweight and absorbs and desorbs sweat easily.

Antiperforation insole

Average 4,00 mm thick, anti-perforation insole, made of Fabric 100% PES, perforation resistance type Y at 1100 N according to the European Standard EN 22568-4:2019

Sole

High wear resistant antistatic bicomponent cemented sole. PU midsole combined with a nitrile rubber tread, oil and petrol resistance, SRC slip resistance and heat resistance at 300° antistatic, high abrasion resistance. The particular structure of the tread gives stability on uneven grounds

Weight/pair

Ca. 860 gr (size. 42)

Back height

Ca. 11,5 cm (sole included) (size. 42)

CE Certificate

EN ISO 20347:2012 O3 HI HRO FO SRC
Category D.P.I. II°

Size range

EU 36 – 49