

3CHAMO CHAMOIX GTX



WORKWEAR & RESCUE



- Combat ankle boot suitable for mountain/forest environment. Suitable also for Search & Rescue operators and for outdoor activities.
- Perfect stability on all surfaces
- Gore-Tex® Performance Comfort Footwear lining, perfect for a wide range of weather conditions and open-air activities
- Waterproof, breathable upper (breathability is 500% higher than the European standard EN ISO 20347 5.4.6 requirement)
- Extremely comfortable to wear all day long, thanks to the PU midsole
- Excellent adhesion on uneven surfaces
- Shock absorption in the heel area is 40% better than the European standard EN ISO 20347 6.2.4 requirement)
- Antistatic, oil and hydrocarbon resistant sole with anti-perforation characteristics thanks to multi-layered technical fabric insole
- Protective rubber banding on the lower part of the upper, all around the boot
- The heat insulation (sandbath) is 30% higher than the European standard EN ISO 20347 6.2.3.1 requirement



Article Description: CHAMOIX GTX

Article Code: 3CHAMO

Upper

Nubuck bovine leather, water-repellent and breathable, brown, thickness 2.4-2.6 mm.

Cuff and bellows tongues

Nubuck lining, water-repellent and breathable, brown, thickness 1.0-1.2 mm.

Banding

Black rubber, thickness 2.0 mm, high abrasion resistance.

Ankle protector

Made of padding with excellent shock-absorption properties.

Lining

Seam sealed 4-layer laminated fabric (GORE-TEX® SPORTIVE), bootie construction:

Layer 1 - 100% PA abrasion resistant lining

Layer 2 - 100% PES felt insert

Layer 3 - Waterproof, breathable ePTFE membrane

Layer 4 - 100% PA protective jersey.

Toe-cap

Non-woven fabric impregnated with thermoadhesive resins and a thickness of 1.8/2.0 mm.

Counter

Non-woven fabric impregnated with thermoadhesive resins and a thickness of 1.8/2.0 mm.

Thread

Polyester thread, highly resistant, 30/3 title, treated for water-repellent properties, brown.

Shoe laces

Round polyester laces, treated for water-repellent properties, brown.

Lacing system

Hooks and eyelets are made of burnished metal. Each shoe is provided with:

- 3 pairs of open hooks at the top, made of rustproof metal
- 1 pair of double-riveted stainless-steel fixing hooks in the middle
- 5 pairs of brass/steel D-rings, applied with a rivet, at the bottom.

Footbed

Removable anatomical footbed, made of thermoformable felt 100% PES, with an upper covering made of non-woven fabric 100% PA.

Insole

Anti-perforation insole with an average thickness of 5.0 mm, made of anti-perforation multi-layered fabric, "Zero mm" at 1100 N in compliance with the EN 12568:2010 standard, with a non-woven fabric cover and integrated by a stabilising polypropylene stay in the lower part.

Sole

Cemented sole consisting of a PU cushioning midsole and Vibram® Fourà nitrile rubber sole, heat resistant at 300°C, antistatic, oils and hydrocarbons resistant and abrasion resistant, shock absorption in the heel area. The structure and peculiar design or the cleats ensure high anti-slip performance; additionally, the sole is equipped with a strengthening toe-bumper, under-cut heel and sculpted waist edge (to increase adhesion on uneven surfaces).

Weight/pair

Abt. 1800 g (size 42)

Height at the back

Abt. 20,5 (sole included) (size 42)

CE Certificate

EN ISO 20347:2012 O3 WR HI AN HRO FO SRA
Category II PPE

Size range

36 – 48